

Mitsubishi PBP16N2 – UCE90132

Année	2020
Heures d'ouverture	979
Configuration	PREMIUM
Attachement type	NO ATTACHEMENT
Battery amperage in A	150
Battery brand	OTHER BRAND
Battery voltage in V	24
Drive roller type	VULKOLLAN
Driving type	WALK-BEHIND
Ext- ext forks width in mm	540
Forks	YES
Forks length in mm	1150
Lift height in mm	0
Load centre in mm	600
Load rollers type	SINGLE WHEEL:TANDEM WHEELS
Steering control	TILLER
Tire type	VULKOLLAN
Type	THIN PLATE PURE LEAD
Version	STANDARD
Weight capacity in kg	1600



[Lien vers la fiche produit](#)

Vérifiez la configuration sur le link:

<https://myusato.cls.it/allestimenti-e-garanzia>

Utilisé comme s'il n'avait jamais été utilisé.



MyUsato® CLS : le choix sûr et pratique pour une flotte capable de réaliser n'importe quelle activité. Commodité, qualité, sécurité et fiabilité : telles sont les principales caractéristiques de l'offre MyUsato, le service proposé par CLS pour répondre aux besoins des entreprises qui ont besoin de renouveler leur parc de machines avec des solutions modernes et fiables.

Le service MyUsato® propose des machines de manutention multimarques avec un excellent rapport qualité-prix : l'objectif est de satisfaire les besoins des clients garantissant la qualité, la sécurité et l'optimisation des coûts.